

<b>Display</b>	Size Screen Type Aspect Ratio Display Area (HxV)mm Resolution (HxV) Pixel Pitch Back Light Unit Response Time Refreshing Frequency Display Color Brightness (typ) Brightness (min) Contrast Ratio (typ) High Haze Viewing Angle Life Time Display Orientation Operation Time	86" LCD 16:9 1895.04(H) × 1065.96(V) 3840(H)×2160(V) 0.4935mm(H) × 0.4935mm(V) DLED 8ms 60Hz 1.07B(10bit) 450 cd/m2 400 cd/m2 1200:1 Yes, Haze 25% 178° 50000 Hours Landscape & Portrait 7 days×24 hours
<b>Connectors</b>	HDMI IN HDMI Output Coaxial/Optical Output Audio Output USB 2.0 USB 3.0 RS232 LAN(RJ45)(10M/100M/1000M) USB Type-C	3(HDMI 2.0) 1(HDMI Daisy chain,Up to 3*3) Optical*1 1,3,5mm 1 (F/W update / Media Play) 1 (F/W update / Media Play) 1 2(IN/OUT) 1(DP1.2,PD 65W,Network Sharing(100M))
<b>System</b>	System Version CPU GPU RAM ROM UI	Android 11 A55*4 MaliG51 MP2 4GB 32GB 4K
<b>Audio</b>	Speaker Type Power	Built-in Speaker 2x10W
<b>Slot</b>	OPS Slot WIFI Slot	Yes, 80 Pin OPS Yes, Included
<b>Mechanisms</b>	Bezel width(T/L/R/B) mm Structure Key Location & Number Handle Dimension (L*W*H) mm Thickness (W/ wall mount) (mm) Wall-hanging Screw VESA (Wall mounting Size) Dimension(package) L*W*H Net Weight(kg) Gross Weight(kg)	15.9/15.9/15.9/15.9 Metal Frame Metal Rear cover Back physical keys, 7 2 1931x1102x81.6 101.4(WIB9080A) M8*25mm 800x600 mm 2110×225×1227mm 43,2 60,8
<b>Power</b>	Power Requirements Standby Power Power Consumption(Typ) Power Consumption(Max)	100-240V~ 50/60Hz ≤0.5W 335W 505W
<b>Accessories</b>	Power Cord By Region Remote Control	3M*1 1 pcs
<b>Environmental Conditions</b>	Operation Temperature Operation Humidity Storage Temperature Storage Humidity Altitude Below	0°C - 40°C 10% - 90% -20°C - 60°C 10% - 90% Below 5000 meters

